

OIL SUCTION & DISCHARGE HOSE 150 PSI

S MAX OSD150

Tank truck, tank wagon suction and delivery hose; it withstand the full vacuum; used for a wide range of petroleum products up to 50% aromatic content.



TEMPERATURE RANGE	- 40°C up to + 100°C
CONSTRUCTION TUBE	Black, smooth, nitrile rubber compound
REINFORCEMENT	High strength synthetic cord helix and anti-static copper wire
COVER	Black smooth (wrapped finish) high grade chloroprene rubber, compounded for an excellent resistance to weather, ozone abrasion and oil
COILS	60 meter (200ft) continuous length; other length available on request
BRANDING	Red transfer tape with negative text
SAFETY FACTOR	4 : 1

PART NO.	I.D.		O.D.		WORKING PRESSURE		BURSTING PRESSURE		BENDING RADIUS (mm)	WEIGHT (nominal) kg/m
	mm	Inch	mm	Inch	bar	psi	bar	psi		
OSD150-0100	25	1	35	1.38	10	150	40	600	103	0.68
OSD150-0125	32	1-1/4	42	1.65	10	150	40	600	125	0.85
OSD150-0150	38	1-1/2	51	2.00	10	150	40	600	151	1.29
OSD150-0175	45	1-3/4	57	2.24	10	150	40	600	173	1.32
OSD150-0200	51	2	62	2.44	10	150	40	600	202	1.70
OSD150-0250	63	2-1/2	77	3.03	10	150	40	600	253	2.67
OSD150-0300	76	3	92	3.62	10	150	40	600	302	2.82
OSD150-0350	90	3-1/2	104	4.09	10	150	40	600	373	3.35
OSD150-0400	102	4	120	4.72	10	150	40	600	453	4.84
OSD150-0500	127	5	147	5.79	10	150	40	600	627	6.49
OSD150-0600	152	6	172	6.77	10	150	40	600	751	7.69
OSD150-0800	203	8	227	8.94	10	150	40	600	1048	8.89
OSD150-1000	254	10	282	11.10	10	150	40	600	1513	19.92
OSD150-1200	305	12	341	13.43	10	150	40	600	1807	28.39

* Other size, pressure ratings and colours available on request