

## SPRING HOSE WIRE REINFORCED HOSE

Heavy-Duty Transparent PVC Hose reinforced with high tensile carbon steel helix. Excellent resistance to pressure vacuum and abrasion. Highly flexible to wide range of temperature.

- Suitable for oil and chemical resistance applications
- Ideal for pumping and transferring of liquid, powder and granular material.
- Exceptionally tough and durable for heavy-duty and discharge - public utilities, drainage, ships, silos and irrigation plants.



PART NO.	INNER DIAMETER (mm)	OUTER DIAMETER (mm)	WORKING PRESSURE (kgf/cm <sup>2</sup> )	WEIGHT (g/m)	COIL LENGTH (m)
SPO09	9	15	8	170	100
SPO12	12	18	6	180	100
SPO15	15	22	6	245	100
SPO19	19	26	5	335	50
SPO22	22	30	5	420	50
SPO25	25	33	5	525	50
SPO28	28	36	4	500	40
SPO32	32	41	4	775	40
SPO35	35	45	4	725	40
SPO38	38	48	4	925	40
SPO41	41	52	4	800	40
SPO45	45	56	4	850	40
SPO48	48	59	4	900	40
SPO50	50	62	3	1375	40
SPO57	57	70	3	2650	20
SPO60	60	74	3	2750	20
SPO63	63	80	2	1765	20
SPO75	75	92	2	2980	20
SP100	100	118	2	4100	10
SP152	152	168	2	6800	10

Internal diameter: + 2%

All technical are subject to + 5% tolerance