

## STEAM HOSE 250 PSI

### S MAX MX250

Mandrel built high pressure wire reinforced steam hose designed for service with superheated steam in heat control, fire prevention etc in many industries at max pressure 1/atm (250 psi)



TEMPERATURE RANGE	40°C (40°F) to + 236°C (+456°F)
TUBE	Black, smooth, pure EPDM rubber specially compounded to withstand super heated steam
REINFORCEMENT	Piles of steel wire cord
COVER	Red, smooth (wrapped finish) EPDM rubber with excellent resistance to high temperature, weathering, abrasion and ageing, it is: pin-pricked to prevent separation
COILS	61 meter (200ft) continuous length; other length available on request
BRANDING	Red cover with embossed tape

PART NO.	I.D.		O.D.		WORKING PRESSURE		BURSTING PRESSURE		WEIGHT (nominal)	
	mm	Inch	mm	Inch	atm	psi	atm	psi	kg/m	lbs/ft
MX250-0050	13	1/2	25	1	17	250	170	2500	0.53	0.36
MX250-0075	19	3/4	32	1-7/32	17	250	170	2500	0.68	0.46
MX250-0100	25	1	39	1-29/64	17	250	170	2500	0.90	0.62
MX250-0125	32	1-1/4	46	1-13/16	17	250	170	2500	1.30	0.87
MX250-0150	38	1-1/2	54	2-1/8	17	250	170	2500	1.60	1.10
MX250-0200	51	2	67	2-41/64	17	250	170	2500	2.20	1.50
MX250-0250	63	2-1/2	83	3-5/16	17	250	170	2500	3.80	2.60
MX250-0300	76	3	95	3-13/16	17	250	170	2500	4.66	3.20
MX250-0400	102	4	124	4-7/6	17	250	170	2500	6.50	4.46

\* Other size, pressure ratings and colours available on request