

WATER HOSE

S MAX 3210B

A heavy duty robust rubber hose for application in shipbuilding, refining, mining, construction industries and petrol chemical industries. Exceeds BS5118 type 2.



TEMPERATURE RANGE	- 30°C up to + 100°C
CONSTRUCTION TUBE	Black, SBR/NR, resistant to oil mist
REINFORCEMENT	High strength synthetic polyester braided (3 ply)
COVER	Blue, smooth synthetic rubber, abrasion and weather resistant
SAFETY FACTOR	4 : 1
COLOUR	Blue
BRANDING	with S MAX - 3210 W.P. 300 PSI printing

PART NO.	INTERNAL DIAMETER		EXTERNAL DIAMETER (mm)	WORKING PRESSURE		BENDING RADIUS (mm)	AVERAGE WEIGHT (kg/m)
	Inch	mm		bar	psi		
S MAX-3210B AWH-0050	1/2	13	23	20	300	102	0.38
S MAX-3210B AWH-0075	3/4	19	32	20	300	153	0.69
S MAX-3210B AWH-0100	1	25	38	20	300	201	0.87
S MAX-3210B AWH-0125	1-1/4	32	45	20	300	248	1.07
S MAX-3210B AWH-0150	1-1/2	38	52	20	300	261	1.42
S MAX-3210B AWH-0200	2	51	67	20	300	305	2.39
S MAX-3210B AWH-0250	2-1/2	63	80	20	300	386	2.81
S MAX-3210B AWH-0300	3	76	93	20	300	455	3.33
S MAX-3210B AWH-0400	4	102	120	20	300	736	4.72

* Other size, pressure ratings and colours available on request